

FEATURES

- 2 microphone & 3 AUX input
- External microphone panel (**MA-1R**) input
- Treble & Bass tone control
- RMS 25W 8 Ohms mono audio power output
- Acceptable for Dynamic/Condenser Microphone
- Flexible input panel location (Side & Bottom)
- Individual Trim control for 2 microphone input
- Auto override function for central broadcasting (Optional)
- 5~10 second delay for override function



SPECIFICATIONS

Power Source	AC 220V/50Hz
Power Consumption	35W
Rated Output Power	25W 8 Ohms
Frequency Response	20 - 20,000Hz \pm 3dB
Distortion	Less than 0.2% (Rated Output Power at 1kHz)
Tone Control	\pm 8 dB at 100Hz, 10,000Hz
Input Circuit	
Mic 1&2	-42dB, 600 Ohms, unbalanced
Aux 1&2	-20dB, 10K Ohms, unbalanced
External Input	For AVS Mic Panel MA-1R Use Only
Speaker Output	4 - 8 Ohms
Dimensions	265(W) x 185(H) x 70 (D) mm
Weight	Approx. 2.6 Kg



R & B COMPUTER SYSTEMS LTD.

力衡電腦系統有限公司

2749 3325

www.rnb.com.hk

rnb@rnb.com.hk

Unit 1009, Global Gateway Tower, 63 Wing Hong Street, Cheung Sha Wan, Kln., HK
香港九龍長沙灣永康街 63 號 Global Gateway Tower 1009 室

Optional Accessories :



Model : MA-1R (Mic Panel)



Passive Override Module ---- Type A



Active Override Module ---- Type B