



DC-I800 PORTABLE VISUALIZER



PORTABLE MECHANICAL ARM DESIGN

ROTATED CAMERA HEAD

HDMI AND VGA BYPASS FUNCTION

ONE TOUCH RECORDING AND PHOTOGRAPH

A3 SHOOTING AREA

THREE SEGMENT DIMMING

MADE IN TAIWAN



SPECIFICATION:

| | |
|-------------------------|---|
| LENS | 4.6~23MM/F2.6~5.9 ; 5X OPTICAL ZOOM |
| WORKING SURFACE | A3 SIZE |
| ZOOM | 5X OPTICAL ZOOM ; 8X DIGITAL ZOOM ; 8X MECHANICAL |
| ZOOM | (TBD) |
| FOCUS | AUTO |
| UPPER | LED ILLUMINATION SYSTEM (3-STAGE BRIGHTNESS CONTROL) |
| LOWER | N/A |
| IMAGE SENSOR | 1/3.2" CMOS SENSOR |
| NUMBER EFFECTIVE PIXELS | 8 MEGA PIXELS |
| STILL IMAGE RESOLUTION | 8MP / 5MP / 2MP |
| HDMI OUTPUT | FULL HD: (1920X1080) :(16:9) :30FPS |
| VGAOUTPUT | XGA:(1024X768) :(4:3) :30FPS |
| CAPTURE TYPE | SINGLE |
| WHITE BLANCE | AUTO |
| BRIGHTNESS | ±7 COMPENSATION |
| IMAGE CONTROL | FREEZE / HIGHLIGHT / MASK / FLIP / PIP / SLIDESHOW |
| IMAGE EFFECT | TEXT / GRAPHICS / B&W / NEGATIVE |
| LCD DISPLAY | N/A |
| REMOTE CONTROL | YES(IR REMOTE CONTROL) |
| MECHANICAL ARM | YES |
| PC CAMERA | YES(640X480 @ 30FPS) |
| RGB OUTPUT | YES(15-PIN D-SUB x1) |
| RGB INPUT | YES(15-PIN D-SUB x1) |
| IO HDMIOUTPUT | YES(19-PIN HDMI 1.3 x1) |
| COMPOSITE OUTPUT | N/A |
| AUDIO OUTPUT | N/A |
| AUDIO INPUT | N/A |
| USB | YES(USB2.0, TYPE B x1) |
| DC 5V INPUT | YES(POWER JACK x1) |
| SDHC CARD SLOT | YES(SUPPORT UP TO 32GB SDHC CARDS) |
| POWER SPURCE | DC 5V, 100-240V, 50-60Hz |
| POWER CONSUMPTION | TBD |
| PACKAGE CONTENT | AC/DC ADAPTER x1 / 15-PIN D-SUB CABLE x1(VGA CABLE) / USB CABLE x1 / HDMI CABLE x1 / BATTERY x2 / REMOTE CONTROL x1 / MICROSCOPE ADAPTER x1 / ANTI-GLARE SHEET x1 / QUICK GUIDE x1 / CD x1 |



R & B COMPUTER SYSTEMS LTD.

力衡電腦系統有限公司

2749 3325

 www.rnb.com.hk
 rnb@rnb.com.hk

Unit 1009, Global Gateway Tower, 63 Wing Hong Street, Cheung Sha Wan, Kln., HK
香港九龍長沙灣永康街 63 號 Global Gateway Tower 1009 室