XJ-F101W





LampFree. MercuryFree. StressFree.

The Casio Advanced Series XJ-F101W projector provides high brightness of 3500 ANSI lumens in WXGA resolution. LampFree® projectors use Casio's Laser & LED light source that eliminates the risk of downtime due to mercury lamp failure. Dust resistant designs with no lamps or filters to replace provide long lasting performance of up to 20,000 hours with minimal maintenance. Two (2) HDMI inputs provide connectivity with all current display technology without the need for switching cables. A high power USB port (DC 5V 2A) provides direct power for USB stick devices and eliminates the need for a separate power supply.

Key Features

- 3500 Lumens
- WXGA (1280 x 800)
- 1.5X Zoom Lens
- 16W Speaker
- · Dust Resistant Design
- DLP® Technology
- 20,000:1 Contrast Ratio

LampFree Features

- · Laser & LED Light Source
- · Long Life, 20,000 hour estimated operating life
- No Lamp replacement required
- No Filters to replace
- Low Power Consumption
- · Mercury Free
- Instant On 5 seconds to full brightness
- Instant Off no cool down required

Terminal Interface





R & B COMPUTER SYSTEMS LTD. 力衡電腦系統有限公司

C 2749 3325

www.rnb.com.hk
rnb@rnb.com.hk

Unit 1009, Global Gateway Tower, 63 Wing Hong Street, Cheung Sha Wan, Kln., HK 香港九龍長沙灣永康街 63 號 Global Gateway Tower 1009 室

Note:

For more images visit www.CasioLampFree.com Designed and Manufactured by CASIO in Japan TAA Compliant

SPECIFICATIONS	XJ-F101W
Native Resolution	WXGA (1280 x 800)
Native Aspect Ratio	16:10
Brightness	3500 Lumens
Display Device	0.65-inch DLP® chip
Contrast Ratio	20,000:1
Lens Type	1.5X Manual Zoom & Focus
Lens Offset	33%
Light Source	Laser & LED
Estimated Light Source Life	Up to 20,000 Hours
Screen Size (Min - Max)	35 to 300-inch diagonal
Projection Range	<u> </u>
60-inch Screen	5.4 ~ 7.9 ft
100-inch Screen	9.2 ~ 13.5 ft
Minimum Throw Distance	3.0 ft
Throw Ratio	1.32 – 1.93:1
Keystone Correction	Vertical +30° (Auto) / Vertical + or - 30° (Manual)
Color Reproduction	Full Color (Up to 1.07 billion colors)
Power Source	AC100~240V, 50/60Hz
Power Consumption	AC100-240V, 30/00112
·	205 W - Light Control "off" and Bright selected
Operating	165 W - Light Control "on" and Light Output 7 selected
Standby	0.12 W
TERMINAL CONNECTIVITY	
Video Signal Compatibility	_
Video Systems	NTSC / PAL / PAL-N / PAL-M / PAL60 / SECAM
DTV / HDTV	480i / 480p / 576i / 576p / 720p / 1080i / 1080p
Maximum Computer Input	WUXGA (1920 x 1200) *Reduced Blanking Signal
INPUTS	Waxax (1720 x 1200) Reduced Statisting Signal
	mini D-Sub 15 pin x 1
RGB/Component Video Input	Also use as YCbCr/YPbPr input – commercially available adapter required
HDMI	HDMI Type A x 2, HDCP and Audio Support
Composite Video	Composite Video (RCA) x1
Audio	RCA (R/L) x 1, 3.5mm Stereo Mini Jack x 1
USB Power Supply	Yes, DC 5V 2A
USB Input (Host)	No No
Logo Transfer	Micro B (USB1.1) x 1
Wireless Capability	No No
	110
OUTPUTS	
OUTPUTS Audio	3 Smm Stereo Mini Jack v1 (variable audio)
Audio	3.5mm Stereo Mini Jack x 1 (variable audio)
Audio AUDIO AND CONTROL SYSTEMS	
Audio AUDIO AND CONTROL SYSTEMS Audio System	16W Monaural Speaker
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN	16W Monaural Speaker
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation)
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft.
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7)	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation
Audio AUDIO AND CONTROL SYSTEMS Audio System R5-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20~80% (non condensation) Yes, for operation 5,000~10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x 2) / AC Power Cord / RGB Cable
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16-4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x2) / AC Power Cord / RGB Cable Warranty and Safety Precautions
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x 2) / A C Power Cord / RGB Cable Warranty and Safety Precautions Soft Carrying Case YB-2
Audio AUDIO AND CONTROL SYSTEMS AUDIO SYSTEMS RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Unit Dimensions w/ Projections	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x 2) / AC Power Cord / RGB Cable Warranty and Safety Precautions Soft Carrying Case YB-2 White 11.8 x 11.8 x 3.8 inches
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Unit Dimensions w/ Projections Unit Dimensions w/o Projections	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16-4 ft Maximum Kensington¹™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x2) / AC Power Cord / RGB Cable Warranty and Safety Precautions Soft Carrying Case YB-2 White 11.8 x 11.8 x 3.8 inches N/A
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Unit Dimensions w/o Projections Unit Dimensions w/o Projections Weight	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x 2) / AC Power Cord / RGB Cable Warranty and Safety Precautions Soft Carrying Case YB-2 White 11.8 x 11.8 x 3.8 inches N/A 8.4 lbs
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Unit Dimensions w/ Projections Unit Dimensions w/o Projections Weight Carton Dimensions	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft. Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x 2) / AC Power Cord / RGB Cable Warranty and Safety Precautions Soft Carrying Case YB-2 White 11.8 x 11.8 x 3.8 inches N/A 8.4 lbs 15.5 x 13.7 x 6.9 inches
Audio AUDIO AND CONTROL SYSTEMS Audio System RS-232 LAN OTHER INFORMATION Operating Temp / Humidity High Altitude Mode Extended Operation (24/7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Unit Dimensions w/o Projections Unit Dimensions w/o Projections Weight	16W Monaural Speaker RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required No 41-95°F / 20-80% (non condensation) Yes, for operation 5,000-10,000 ft. Yes, Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors M4 x 4 (not included) / Insert Depth 5-8mm 3 years Parts and Labor, plus 3 years or 6,000 hours light source Wireless Remote Control / Batteries (AAA x 2) / AC Power Cord / RGB Cable Warranty and Safety Precautions Soft Carrying Case YB-2 White 11.8 x 11.8 x 3.8 inches N/A 8.4 lbs

©2019 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at the time of publication. All specifications and features subject to change without notice. DLP is a trademark of Texas Instruments, XGA is a registered trademark of IBM Corp. in the US. HDMI is a trademark of HDMI Licensing, Ltc. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.* Enhanced Presentation Solutions available only with Network models. Optional YW-41 required. C-Connection Software or App required.

